

Engine Flush

Revision date: 13.03.2025

Product code: 1398

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Engine Flush

UFI: Y367-HJYH-PEJX-32UK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent for Engines

1.3. Details of the supplier of the safety data sheet

Company name: CTP GmbH
Street: Saalfelder Strasse 35h
Place: D-07338 Leutenberg
Telephone: +49 (0)36734 230-0
E-mail: msds@bluechemgroup.com
Contact person: Jens Moeller, Dipl.-Chem.
Internet: www.bluechemgroup.com

Telefax: +49 (0)36734 230-22

Telephone: +49 (0)36734 230-19

1.4. Emergency telephone

GBK GmbH: +49-(0)6132-84463 (24/7)

number:

Further Information

Article Number: 3001, 1001, 1002, 1004, 1005, 1007, 1008, 1009

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Asp. Tox. 1; H304
Lact.; H362
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics
Chlorparaffines C14-C28

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways.
H362 May cause harm to breast-fed children.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P260 Do not breathe vapour/aerosole.
P263 Avoid contact during pregnancy and while nursing.

Engine Flush

Revision date: 13.03.2025

Product code: 1398

Page 2 of 9

P270 Do not eat, drink or smoke when using this product.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of this material and its container to hazardous or special waste collection point.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H304-H362-H412

Precautionary statements

P101-P102-P301+P310-P331-P405-P501

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Anti Friction Components
Detergents, Dispersants
Synthetic agent combinations
corrosion preventing agent

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (GB CLP Regulation)	
	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics	95 - < 100 %
	918-481-9	01-2119457273-39
	Asp. Tox. 1; H304 EUH066	
85535-85-9	Chlorparaffines C14-C28	1 -< 2 %
	287-477-0	01-2119519269-33
	Lact., Aquatic Acute 1, Aquatic Chronic 1; H362 H400 H410 EUH066	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	918-481-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics	95 - < 100 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
85535-85-9	287-477-0	Chlorparaffines C14-C28	1 -< 2 %
	inhalation: LC50 = 48170 mg/l (vapours); dermal: LD50 = 4000 mg/kg; oral: LD50 = 4000 mg/kg		

SECTION 4: First aid measures

Engine Flush

Revision date: 13.03.2025

Product code: 1398

Page 3 of 9

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .
Subsequently wash off with: Water and soap.
Seek medical attention if problems persist.

After contact with eyes

Remove contact lenses.
Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. After ingestion of absorption substances: Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.
After ingestion: Harmful: may cause lung damage if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder. Sand. Carbon dioxide (CO₂). alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.
In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.
Beat down gas/vapours/mist with water spray.
Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear a self-contained breathing apparatus and chemical resistant suit.
Keep away from sources of ignition - No smoking.
Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.
Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Revision date: 13.03.2025

Engine Flush

Product code: 1398

Page 4 of 9

Other information

Prevent spreading of spillages (e.g. by oil barrier).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

The substance should only be handled in closed apparatus or systems. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

Take off immediately all contaminated clothing

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin and eyes.

Keep away from food, drink and animal feeding stuffs.

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Do not store at temperatures over: 50 °C

Take precautionary measures against static discharges.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of fire: Wear self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: green

Engine Flush

Revision date: 13.03.2025

Product code: 1398

Page 5 of 9

Odour:	aromatic	
Boiling point or initial boiling point and boiling range:		180 - 220 °C
Flash point:		65 °C
Auto-ignition temperature:		> 200 °C
Viscosity / kinematic: (at 100 °C)		< 1,0 mm ² /s
Water solubility: (at 20 °C)		insoluble
Solubility in other solvents Organic solvents		
Vapour pressure: (at 20 °C)		20 hPa
Density (at 20 °C):		0,7975 g/cm ³
Bulk density (at 20 °C):		797,5 kg/m ³

9.2. Other information

Other safety characteristics

Pour point: < -20 °C

Further Information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.
No decomposition when used as intended.

10.5. Incompatible materials

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Engine Flush

Revision date: 13.03.2025

Product code: 1398

Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
85535-85-9	Chlorparaffines C14-C28				
	oral	LD50 4000 mg/kg	Rat		
	dermal	LD50 4000 mg/kg	Rat		
	inhalation (1 h) vapour	LC50 48170 mg/l	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

May cause harm to breast-fed children. (Chlorparaffines C14-C28)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics					
	Acute fish toxicity	LC50 1000 mg/l	96 h	Oncorhynchus mykiss		
	Acute algae toxicity	ErC50 1000 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 1000 mg/l	48 h	Daphnia magna (Big water flea)		
85535-85-9	Chlorparaffines C14-C28					
	Acute algae toxicity	ErC50 3,2 mg/l	96 h	Algae		

12.2. Persistence and degradability

Engine Flush

Revision date: 13.03.2025

Product code: 1398

Page 7 of 9

No information available.

12.3. Bioaccumulative potential

Low potential of bio-accumulation.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Arrange about the exact waste code with the local waste disposal expert.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Contaminated packaging

Container must be completely emptied.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Other applicable information (land transport)

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

Other applicable information (marine transport)

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

Other applicable information (air transport)

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

Engine Flush

Revision date: 13.03.2025

Product code: 1398

Page 8 of 9

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
Chlorparaffines C14-C28

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2010/75/EU (VOC): 96,5 % (769,588 g/l)

2004/42/EC (VOC): 96,5 % (769,588 g/l)

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

Contains:
> 30 % hydrocarbons, aliphatic.

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics
Chlorparaffines C14-C28

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,9,11,12,15.

Abbreviations and acronyms

Asp. Tox: Aspiration hazard
Lact: Lactation effects
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method
Lact.; H362	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
H362 May cause harm to breast-fed children.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Engine Flush

Revision date: 13.03.2025

Product code: 1398

Page 9 of 9

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)